

SCANGRIP
EX PROOF **ATEX anti-explosion work lights**



Range of innovative and high performance anti-explosion work lights, built with suitable characteristics to work in absolute safety in environments with a potential explosion risk, in the presence of flammable liquids or gases

Approved and certified in accordance with directive ATEX 2014/34/EU and with directive IECEx for use in hazardous environments:

- Gas zones 1 and 2
- Dust zones 21 and 22

They provide intense and long-lasting light

Mod. MIDI EX

Rechargeable **COB LED flashlight and work light, with 2 levels of intensity**

Robust body, suitable for very humid and dirty environments, with comfortable and ergonomic handle

Main light: 1) 100 lumen - 140 lux at 0,5 m
2) 280 lumen - 200 lux at 0,5 m

Operating time approx. 2,5h / 5h (step 1 / 2)

Spotlight: SMD LED: 100 lumen - 600 lux at 0,5 m

Approx. operating time 2h

Lithium iron phosphate battery, 3,8V (1600 mAh) - Approx. charging time 3,5h

Operating temperature -10° ÷ +45°C

With joint to tilt the light up to 180°, magnet, folding hook and clip for attaching to a belt

Provided with charger with USB port N 9097/85 and USB cable

Dimensions 50x181x29 mm - Weight 180 g

Code N 9133 1000	N 9133/1	Each €	1
-------------------------	-----------------	--------	---



Mod. UNI EX

Rechargeable **COB LED torch and work lamp with 2 levels of intensity** and charging station

Robust body, suitable for very humid and dirty environments, with comfortable and ergonomic handle

Main light: 1) 150 lumen - 190 lux at 0,5 m
2) 290 lumen - 380 lux at 0,5 m

Approx. operating time 6h / 3h (step 1 / 2)

SPOT SMD LED light: 95 lumen - 350 lux at 0,5 m - Approx. operating time 3 h

Lithium iron phosphate battery, 3,2 V (2800 mAh) - Approx. charging time 4 hours

Operating temperature -20° ÷ +45°C

With battery charge indicator on the front, joint to tilt the lamp up to 180°, magnet and swivel hook

Provided with charger with USB port and USB cable

Dimensions 70x220x39 mm - Weight 420 g

Code N 9133 3000	N 9133/3	Each €	1
-------------------------	-----------------	--------	---



Type with sturdy die-cast aluminium body, slim design with hard shockproof rubber profile
Ideal for inspecting large surfaces and for lighting a specific area

Mod. NOVA -EX

COB LED with 2 levels of intensity: 1) 1000 lumen - 1600 lux at 0,5 m
2) 2000 lumen - 3200 lux at 0,5 m

Operating temperature -20 °C to +45°C

Power supply from 100-240V / AC 50-60Hz

Provided with **10 m power cable** for power supply from 100-240V / AC 50-60Hz mains with Schuko plug

With built in carry handle and rear support for positioning the lamp at the desired angle, also usable as a hook or for fastening directly to the tripod

Dimensions 270x266x123 mm - Weight 4 Kg

Code N 9135 1000	N 9135/1	Each €	1
-------------------------	-----------------	--------	---



Mod. NOVA -EX R

COB LED with 2 levels of intensity: 1) 750 lumen - 1200 lux at 0,5 m
2) 1500 lumen - 2400 lux at 0,5 m

Operation time approx. 2 h / 4 h (step 1 / 2)

Rechargeable Lithium-iron-phosphate battery, 19,2 V (1400 mAh) - Charging time about 2 h

Operating temperature -20 °C ÷ +45 °C

Provided with 5 m power cable for power supply from 100-240V AC / 50-60Hz mains with Schuko plug

With built in carry handle and rear support for positioning the lamp at the desired angle, also usable as a hook or for fastening directly to the tripod

Dimensions 270x266x123 mm - Weight 3,9 kg

Code N 9135 6000	N 9135/6	Each €	1
-------------------------	-----------------	--------	---

