ϵ

Professional models, explosion-proof and ATEX certified

Particularly suitable for inspection and maintenance work

With body in synthetic resin, shockproof and waterproof

Mod. UK 4AA eLED Herculite

Resistant to chemical products like acetone, battery acid, brake fluid,

Diesel fuel, ethanol, coolant, petrol, grease, hydrochloric acid,

hydraulic fluid, butanone

Luminous flux 180 lm - Operating time 8h

ON/OFF button

Waterproof to a depth of 3 m

With safety valve for releasing hydrogen vapours which

may develop in batteries

Does not conduct electricity

Works with 4 Alkaline batteries AA LR6 1.5 V (included)

Length 160 mm - Weight 158 g

With loop for helmet elastics using designated hook N 9098/5

Code N 9098 4300 N 9098/43 Each € 1







Zone 2 II 3G ec IIb T4 II 3D IIIB T 132°C

Mod. UK 3AAA e LED VIZION I

LED headlamp with removable lamp module

With luminous flux in 3 different modes: concentrated, diffused

and diffused in red, land spotlight with reduced height and minimum dimensions, yet very efficient (CPO) - Suitable for attaching to protective helmets, caps etc.

Can be immersed in water up to 3 m and resists low temperatures On/off side button

With **TRS system (Thermal Recovery System)** to retrieve the heat produced by LEDs and to transmit it to batteries, extending their lifespan and making the light beam more efficient

Luminous flux 65/35 lm - Luminous flux max length with spot/diffuse beam pattern 60/39 m With 3 1,5V AAA alkaline batteries (approx. operation time direct/diffuse light 13/17 h)

Supplied with non-allergic fabric - Overall length 76 mm - Weight 110 g







67

Light beam adjustable in 3 modes:

- 1) direct,
- 2) widespread,
- 3) diffuse red color

Mod. UK 3AAA VIZION Z3 Herculite

LED headlamp with extractable light module

Resistant to chemical products like acetone, battery acid, brake fluid, Diesel fuel,

ethanol, coolant, petrol, grease, hydrochloric acid,

hydraulic fluid, butanone

With luminous flux in 3 different modes; concentrated, diffused and

diffused in red, and spotlight with reduced height and minimum dimensions,

yet very efficient (CPO) - Suitable for use on protective helmets, hats, etc.

Waterproof to a depth of 3 m

On/off side button - Electrically non-conductive

LED with 3 intensity settings: 1) 210 lm (Operation time approx. 3,5h)


2) 110 lm (Operation time approx. 6,5h)

3) 40 lm (Operation time approx. 32h)

Complete with 3 AAA Alkaline batteries (included)

Complete with adhesive support for helmets N 9098/81

Overall lenght 74 mm - Weight 110 g









Withh LED lamp
Light beam adjustable in 3 modes:

1) direct,

2) widespread,

3) diffuse red color



Accessories for flashlights

Hook for flashlights N 9098/2 and N 9098/72

In synthetic resin - For fixing the flashlights to caps, protective helmets, etc.

Suitable for attaching to the helmet M 3462

 Code N 9098 5000
 N 9098/5
 Each €

Adhesive support

To be applied to the front of protective helmets

Quick release with one hand

 Code N 9098 8100
 N 9098/81
 Each €

Rubber elastic band

Suitable for headlamp application to protective

helmets for non-slip grip

Suitable for flashlights N 9098/8 and N 9098/83

 Code N 9098 8110
 N 9098/811
 Each €







