

Impact wrenches



A 9

ABC tools

Light body in composite material and high-resistance nylon fiber with thermoinsulated ergonomic handle

Back air expulsion through the handle - **Reversible**

With **double hammer mechanism**

Impact regulation in 3 positions for right rotation and 1 position for left rotation

Air threaded coupling 3/8" Gas for hoses with internal Ø 10 mm

For bolts up to M 13

Working torque 380 Nm - Max tightening torque 433 Nm

Impacts/min 1200 - Max idle rpm 10000 - Air consumption 1,9 l/sec

Idle noise 91,4 dB(A) - Idle vibrations 4,4 m/s² - Weight 1,2 kg

Code E 1126 0000	E 1126/0	Each €	1
------------------	-----------------	--------	---

**ABC** tools - AUTOMOTIVE LINE

Light body in composite material and nylon fiber, high-resistant, with thermoinsulated handle

With **powerful double hammer mechanism**

Percussion regulation in 3 stages for right rotation - **Reversible**

Back air expulsion through handle

Threaded coupling 1/4" Gas pipes with internal Ø 10 mm

For bolts up to M 16

Max working torque: suggested 542 Nm - tightening 740 Nm - untightening 1288 Nm

Impacts/min 1000 - Max idle rpm 7500 - Air consumption 2,1 l/sec

Idle noise 85,8 dB(A) - Idle vibrations 8,4 m/s² - Weight 2 kg

Code E 1126 2500	E 1126/25	Each €	1
------------------	------------------	--------	---

**ABC** tools - INDUSTRIAL LINE

Light body in composite material and high-resistance nylon fiber with thermoinsulated handle

Back air expulsion through the handle - **Reversible**

With **double hammer mechanism**

Percussion regulation in 3 positions for right rotation and 1 position for left rotation

Air threaded coupling 3/8" Gas for hoses with internal Ø 10 mm

For bolts up to M 29

Working torque 1356 Nm - Max tightening torque 1491 Nm

Impacts/min 750 - Max idle rpm 4500 - Air consumption 2,7 l/sec

Idle noise 96,6 dB(A) - Idle vibrations 6,2 m/s² - Weight 3,8 kg

Code E 1126 4900	E 1126/49	Each €	1
------------------	------------------	--------	---

**HAZET**

Ultra-light magnesium body with thermoinsulated handle

With **powerful double hammer mechanism** that develops a soft and balanced stroke and ensures higher power with less vibrations - Back air expulsion - **Reversible**

Percussion regulation in 3 positions for right and left rotation

Threaded coupling 1/2" Gas hoses with internal Ø 19 mm

For bolts up to M 36

Working torque 2440 Nm - Max tightening torque 2712 Nm

Impacts/min 750 - Max idle rpm 6200 - Air consumption 4,5 l/sec

Idle noise 104 dB(A) - Idle vibrations 12,5 m/s² - Weight 6,8 kg

Code E 1126 5600	E 1126/56	Each €	1
------------------	------------------	--------	---

**GRASSO**®

High-resistance aluminium body

With **powerful double hammer mechanism** - Excellent weight-power ratio

With additional side handle

Threaded coupling 1/2" Gas for hoses with internal Ø 16 mm

Back air expulsion with deflector - **Reversible**

Straight version with internal start-up lever

For bolts up to M 55

Working torque 1177÷2943 Nm - Max tightening torque 5297 Nm

Impacts/min 650 - Max idle rpm 3200 - Air consumption 27 l/sec

Idle noise 102,5 dB(A) - Idle vibrations 7,6 m/s² - Weight 15,3 kg

Code E 1126 8055	E 1126/8	Each €	1
------------------	-----------------	--------	---

