

KNIPLEX Circlip pliers for external circlips

In forged chrome-vanadium, oil-hardened steel
Thermoplastic coated handles - With spring $\overline{\text{MM}}$ - Strong shape, forged

For shafts (external rings)

With straight jaws (DIN 5254 A)

Standard version - Polished head - 1

Size	Code	B 1752/2 Each €	For rings Ø mm	Overall length mm	pcs.
0	B 1752 2000		3÷10	140	6
1	B 1752 2001		10÷25	140	6
2	B 1752 2002		19÷60	180	6
3	B 1752 2003		40÷100	210	6
4	B 1752 2004		85÷140	320	6
5*	B 1752 2005		122÷300	560	1
6*	B 1752 2006		252÷400	570	1

* In sheet steel with interchangeable tips

Spare tips for B 1752/2 sz. 5 - 6


Suitable for size	5	6
Code	B 1752 3005	B 1752 3006
B 1752/3 Per pair €		

Precision execution - Reduced and phosphated head

B 1752/5 - With adjustable stop to limit the opening of the head

Size	Code	B 1752/4 Each €	Code	B 1752/5 Each €	For rings Ø mm	Overall length mm	pcs.
0	B 1752 4000		B 1752 5000		3÷10	140	6
1	B 1752 4001		B 1752 5001		10÷25	140	6
2	B 1752 4002		B 1752 5002		19÷60	180	6
3	B 1752 4003		B 1752 5003		40÷100	225	6
4	B 1752 4004		—		85÷140	320	6

For shafts (external rings)



3÷10 - 85÷140 mm



* sz. 122÷300 - 252÷400 mm:
in sheet steel with interchangeable tips



Large contact surface:
it makes it difficult for the ring to
come out and provides a more
secure grip



B 1752/4



B 1752/5

With adjustable
stop to limit the opening of the head

With jaws bent at 45°

Standard version - Polished head - 1

Size	Code	B 1753/1 Each €	For rings Ø mm	Overall length mm	pcs.
0	B 1753 1000		3÷10	130	6
1	B 1753 1001		10÷25	130	6
2	B 1753 1002		19÷60	185	6
3	B 1753 1003		40÷100	210	6
4	B 1753 1004		85÷140	310	6



∠45°

With jaws bent at 90° (DIN 5254 B)

Standard version - Polished head - 1

Size	Code	B 1753/2 Each €	For rings Ø mm	Overall length mm	pcs.
0	B 1753 2000		3÷10	125	6
1	B 1753 2001		10÷25	125	6
2	B 1753 2002		19÷60	165	6
3	B 1753 2003		40÷100	200	6
4	B 1753 2004		85÷140	300	6
5*	B 1753 2005		122÷300	570	1
6*	B 1753 2006		252÷400	580	1



∠90°



∠90°

* sz. 122÷300 - 252÷400 mm:
in sheet steel with interchangeable tips



B 1753/4



B 1753/5

With adjustable
stop to limit the opening of the head