

KNIPEX Crimping pliers for end sleeves (ferrules)

For crimping ferrules conforming to DIN 46228 (part 1+4)

For 0,5÷6,0 mm² terminals (AWG 20-10)

Front crimping ideal for hard-to-reach places

In special, forged, oil-hardened steel

Synthetic resin coated handles - With one notch - Overall length 180 mm

Code B 2193 5800 **B 2193/58** Each €  6

For 0,25÷16 mm² terminals (AWG 23-5)

In special forged, oil-hardened steel

Two-component handles with hand guard - With 9 notches - Overall length 180 mm

Code B 2193 6000 **B 2193/6** Each €  6

With automatic adjustment according to different conductor sections, to ensure a comfortable, fast and safe crimping - Patented model

Parts subject to crimping **in special, oil-hardened steel**, burnished head

Very thick, ergonomic two-component handles for the highest operating ease

With crimping force, factory calibrated - Unremovable locking for secure connections

Crimping force increased by lever transmission

Version for lateral crimping with hexagonal section,

Ideal for hard-to-reach places

For terminals 0,08÷10 mm² (AWG 28-7)

Overall length 180 mm

Code B 2193 6100 **B 2193/61** Each €  1

Version for lateral crimping with squared section, ideal for

obtaining great contact surfaces regardless

of the connection position

For terminals 0,08÷10 + 16 mm² (AWG 28-7+5)

Overall length 180 mm

Code B 2193 6200 **B 2193/62** Each €  1

Version for frontal crimping with squared section,

Ideal for obtaining great contact surfaces

regardless of the connection position

With front insertion particularly suitable for

hard-to-reach places (i.e. electrical panels)

Overall length 190 mm

For ferrules	mm ²	0,08÷10*	0,08÷10 ÷ 16
Code		B 2193 6310	B 2193 6316
B 2193/63	Each €		
AWG		28-7	28-7 + 5

* Also suitable for lateral crimping up to 2,5 mm²

End sleeves (ferrules) with collar - DIN 46228/4

In tinned electrolytic copper, with polypropylene insulation -55°C÷+105°C°

Sold in packs as indicated in the table

B 2193/64 - For single cable

B 2193/65 - For two cables (for crimping cables with the same section)

For cables	mm ²	0,5	1	1,5	2,5	4	6	10
Code	B 2193 ...	6405	6401	6415	6425*	6404*	6406	6410
B 2193/64	Per pack €							
Code	B 2193 ...	6505	6501	6515	6525	6504	6506	6510
B 2193/65	Per pack €							
Color		white	red	black	blue	grey	yellow	red
B 2193/64	d ₁ - L ₁ - L ₂ mm	1-8-14	1,4-8-14	1,7-8-14	2,2-8-14	2,8-10-17	3,5-12-20	4,5-12-22
B 2193/65	d ₁ - L ₁ - L ₂ mm	1,4-8-15	1,95-8-15	2,2-8-16	2,8-10-18,5	3,7-12-23	4,8-14-26	6,4-14-26
In pack of	pcs.	500	500	500	250	100	100	100

* In 500 pieces pack

KNIPEX

Pre-insulated end sleeves assortment - DIN 46228/4

In strong, **high resistance synthetic resin box** «TANOS MINI-systainer», with practical mounting system to pile up several boxes

Consisting of:

1 plier type B 2193/6 for terminals 0,5÷16 mm with coated handles in synthetic resin

200 end sleeves 0,5 mm² white

200 end sleeves 0,75 mm² gray


200 end sleeves 1,0 mm² red

200 end sleeves 1,5 mm² black

150 end sleeves 2,5 mm² blue

Box dimensions LxDxh 267x170x70 mm

Code B 2193 6700 **B 2193/67** Each €  1



B 2193/64



B 2193/65

