


Open brass terminals

For solderless connections
Particularly suitable for auto electricians
Sold in indivisible packs of 100 pieces

For cable connections with section from 0,5 to 1 mm² (AWG 22-17)


Flat male connector

Pin width	mm	6,3
Code		B 2196 1163
B 2196/11	Per pack €	
Dimensions d ₂ x w	mm	8,8x20



Flat female socket type


Pin width	mm	6,3
Code		B 2196 1263
B 2196/12	Per pack €	
Dimensions d ₂ x w	mm	7,4x19,2



For cable connections with section from 1,5 to 2,5 mm² (AWG 16-14)


Eyelet connector - DIN 46225

Screw hole	mm	5,3
Code		B 2196 2553
B 2196/25	Each €	
Dimensions d ₃ x L ₁	mm	9,5x17,5




Flat male connector

Pin width	mm	6,3
Code		B 2196 2663
B 2196/26	Per pack €	
Dimensions d ₂ x w	mm	8,8x20



Flat female socket connector


Pin width	mm	6,3
Code		B 2196 2763
B 2196/27	Per pack €	
Dimensions d ₂ x w	mm	7,4x19,2



For cable connections with section from 4 to 6 mm² (AWG 12-10)


Flat male connector

Width	mm	6,3
Code		B 2196 4663
B 2196/46	Per pack €	
Dimensions d ₂ x w	mm	8,8x20



Flat female socket connector

Pin width	mm	6,3
Code		B 2196 4763
B 2196/47	Per pack €	
Dimensions d ₂ x w	mm	7,4x19,2



Polyethylene terminal covers

With back insertion

For flat female terminal (B 2194/7 - B 2195/7 - B 2196/7)

For pin width	mm	6,3
Code		B 2196 4863
B 2196/48	Per pack €	
Dimensions L x W x H	mm	22/9,3*



For flat male terminal (B 2194/8 - B 2195/8 - B 2196/8)

For pin width	mm	6,3
Code		B 2196 4963
B 2196/49	Per pack €	
Dimensions L x W x H	mm	22/12*

