

ABC TOOLS Water pump pliers

In forged, oil-hardened, chrome-vanadium steel

With double guide continuous hinge pin for great stability and guard between the handles to prevent operators' fingers being pinched

Combined, concave toothed and straight knurled jaws

Approx. hardness tempered teeth 55-60 HRC, wear resistant, for a firm grip

Painted execution with naked handles

With **7 adjustment positions** - Polished head

For pipes Ø inches 1/8÷1 1/4

Min-max jaws width 6÷32 mm

Overall length 240 mm

Code B 2313 6240	B 2313/6	Each €	 6
-------------------------	-----------------	--------	---



Burnished version with handles coated in thermoplastic resin

Clean head

Overall length	mm	200	250	300
Code		B 2313 7200	B 2313 7250	B 2313 7300
B 2313/7	Each €			
For pipes Ø max.		1 1/2" (38 mm)	2" (50 mm)	2 1/2" (65 mm)
For nuts max.	mm	38	50	65
Adjustments		9	9	9



B 2314/1 length 180 mm



B 2314/1 length 240 mm



B 2314/1 length 400 mm

Automatic opening adjustment on the workpiece itself, push-button operated

Thermoplastic resin coated handles - Clean head

Overall length	mm	150	180	240	300	400
Code	B 2314	1150	1180	1240	1300	1400
B 2314/1	Each €					
For pipes Ø max.	inches	1 1/4	1 1/2	2	2 3/4	3 1/2
For pipes Ø max.	mm	32	40	50	70	90
For nuts max.	mm	30	36	46	60	95
Adjustments	n°	15	18	24	31	29

KNIPPEX Water pump pliers

In forged, oil-hardened, chrome-vanadium steel - DIN ISO 8976

With **double guide** continuous hinge pin for great stability and guard between the handles to prevent operators' fingers being pinched - Combined, concave toothed and straight knurled jaws

Self-locking, firm grip on the workpiece, and minimum force required

Approx. hardness tempered teeth 61 HRC, wear resistant, for a firm grip

B 2314/5 - Thermoplastic coated handles - Polished head

B 2314/7 - Very thick two-component handles - Polished head

B 2314/8 - Very thick two-component handles - Chromed head

B 2314/9 - **With safety lug welded to the handle** for use with a lanyard safety to engage with fall protection

Max load admitted 400 N

Overall length	mm	180	250	300	400
Code		B 2314 5180	B 2314 5250	B 2314 5300	B 2314 5400
B 2314/5	Each €				
Code		—	B 2314 7250	B 2314 7300	—
B 2314/7	Each €				
Code		B 2314 8180	B 2314 8250	B 2314 8300	—
B 2314/8	Each €				
Code		—	B 2314 9250	B 2314 9300	—
B 2314/9	Each €				
For pipes Ø max.	inches	1 1/4	2	2 3/4	3 1/2
For pipes Ø max.	mm	32	50	70	90
For nuts max.	mm	30	46	60	95
Adjustment options	n°	7	9	9	11

Mod. "Alligator®"



B 2314/5



B 2314/7




B 2314/8



B 2314/9



Version with highly insulating VDE coating

Chromed head -  6 pcs.

Overall length	mm	250	300
Code		M 7140 0250	M 7140 0300
M 7140	Each €		
For pipes Ø max.	inches	2	2 3/4
For pipes Ø max.	mm	50	70
For nuts max.	mm	46	60
Insulated handles		two-component	immersion



250 mm
   1000 V

IEC/DIN EN 60900



300 mm