

Manufactured according to 73/362/CEE European standards The prices indicated include checking and punching

LENGHT 2 m

Plastic springs, pass-through and clinched rivets Degree scale on the joint of the first section

White with black numbers








Duraluminium levels

FABC TOOLS

In tubular profile 50x22 mm

Accuracy ±1 mm/m

Simple base and 2 vials with lenticular effect





0 0











** Cutting discs for portable machines

Reinforced with high strength glass fibers - High abrasive power Statically and dynamically balanced

80 m/s peripheral speed

Hole Ø 22,23 mm (16 mm for Ø 100 mm)

For cutting

i or outling					
Diameter	Ø mm	115	125	180	230
Code		D 9813 0115	D 9813 0125	D 9813 0180	D 9813 0230
D 9813	Each €				
Rotational speed	rpm	13300	12250	8500	6650
3	pcs.	25	25	25	25



FLEX Angle grinders

Light version for precision works with minimum effort and great value for money

Carbon brushes with automatic stop before compete wear

With locking button on the grinding wheel holder shaft

Supplied with additional handle for left and right hand use, protection cover and fixing flange Without discs

For discs Ø 115 mm

Absorbed power	W	750			
Idle speed	rpm	11000			
Threaded shaft attac	hment	M 14			
Weight	kg	1,8			
Code E 1113 2000	E 1113/2	Each €	> 1		



Protective gloves for industrial use

Type with synthetic leather palm with PVC non-slip inserts

Conforms to CE, Category II

Back in double layer elasticised fabric

Neoprene knuckle guards and thumb in spongy fabric

Elasticised wrist closer with Velcro strip

Length 250 mm - Size 10

Code M 2268 5700





Helmets

ABC TOOL

Entirely in high density polyethylene

With reinforcing ribbing and sweat protection Equipped for fixing earmuffs and protective visor

Inner webbing adjustable from size 52 to 60

THIS TODONING CANADIC TO THE CLASS OF THE CO.						
Colour	White	Yellow				
Code	M 3462 0001	M 3462 0000				
M 3462 Ea	ıch €					

