

With cylindrical shank**In chrome-vanadium steel** - With two cutting edges and centering point**Long version** - With reduced shank Ø 12 mm -  pcs. 1

Diameter	mm	6	8	10	12	14
Code		B 5371 0006	B 5371 0008	B 5371 0010	B 5371 0012	B 5371 0014
B 5371	Each €					
Cylindrical shank Ø	mm	6	8	10	10	10
Overall length	mm	240	240	240	240	240
Diameter	mm	16	18	20	22	24
Code		B 5371 0016	B 5371 0018	B 5371 0020	B 5371 0022	B 5371 0024
B 5371	Each €					
Cylindrical shank Ø	mm	10	10	10	13	13
Overall length	mm	250	250	250	250	250




B 9

With attachment 1/4" - E 6,3 - DIN 3126 - In high speed steel - HSS

Ground, high precision - C-shape sharpening, with centering point

Suitable for battery-powered screwdriver drills and also connectors for inserts

For holes in soft and hard wood, cardboard fibers, masonite panels - 1  pce

Diameter	mm	3	4	5	6	8
Code		B 5372 0003	B 5372 0004	B 5372 0005	B 5372 0006	B 5372 0008
B 5372	Each €					
Overall length	L mm	75	90	100	110	120

Attachment
1/4" - E 6,3**Set of 4 bits B 5372** Ø 3 - 4 - 5 - 6 mm - In plastic case

Code B 5372 4000	B 5372/4	Each €	 1
-------------------------	-----------------	--------	---



Shell countersinks - 90°
In special steel - Used with B 5368 drill bits - Suitable for drilling and countersinking efficiently and in one single operation - With threaded grub screw for shank fixation

For drills Ø d	mm	3	4	5	6	8	10
Code	B 5373 ...	0003	0004	0005	0006	0008	0010
B 5373	Each €						
Diameter D	mm	16	16	16	16	20	20



Boarding augers
In chrome-vanadium steel - With carefully tempered **cylindrical shank****High concentric precision of the point**


For construction, drilling cement formwork and armatures in one single pass, also suitable for sanitary, heat and electrical systems, pipes running through wood, plaster plates and light, prefabricated building elements as well as light materials

The point is slightly conical to allow easy removal

NOT suitable for concrete and stone - **Without welds****B 5374/4** - Overall length 400 mm**B 5374/6** - Overall length 600 mm

Diameter	mm	8	12	14	16	18	20	22	24
Code		B 5374 4008	B 5374 4012	B 5374 4014	B 5374 4016	B 5374 4018	B 5374 4020	B 5374 4022	—
B 5374/4	Each €								
Code		B 5374 6008	—	B 5374 6014	—	B 5374 6018	B 5374 6020	B 5374 6022	B 5374 6024
B 5374/6	Each €								
Cylindrical shank Ø	mm	6	8	8	10	10	10	10	11



Mortise bits
In special steel - Cylindrical shank Ø 16 mm - Shank length 50 mm - With 2 straight right-hand grooves with alternating chip-breaker teeth on the cutting edges -  10 pcs.

Diameter	mm	6	8	10	12	14	16	18	20
Code	B 5376 ...	0006	0008	0010	0012	0014	0016	0018	0020
B 5376	Each €								
Overall length	mm	120	130	140	150	160	170	180	185

