

Special plastic material resistant to corrosion by acids, oils and solvents

Capacity 1 litre

C 3265/4 Code C 3265 4000 **>** 1



With grip cap Overall length 110 mm

C 3265/5 Code C 3265 5000 Each € **12**



Hazer Set for battery service

Set made up of:

- 1 container capacity 4 I for distilled water, in unbreakable rubber resistant to acids with tool compartment
- 1 screwdriver 100x4 mm Mod. 803-40 (A 1436/5)
- 2 open end wrenches 10x11 and 12x13 mm Mod. 450N (A 2928)
- 1 adjustable jaws 255 mm Mod. 760N-2
- 1 brush for poles and terminals Mod. 4650-4 (C 3265/5)
- 1 rubber syringe Mod. 4650-0 (C 3266/1)
- 1 tester- Mod. 4650-1 (C 3266/2)
- 1 extractor for terminals Mod. 4650-2

Dimensions 280x135x245 mm - Weight complete 2,8 kg

Code C 3266 0000 C 3266/0 **>** 1 Each €



HAZET Battery filling tool

Rubber

Pear Ø 68 mm

Total length 256 mm

Code C 3266 1000 C 3266/1 Each € **3** 1



Hydrometer for batteries

For checking electrolyte density

With areometer

C 3266/15 - Pear Ø 30 mm - Overall length 210 mm C 3266/2 - Pear Ø 50 mm - Overall length 280 mm

Code C 3266 1500	C 3266/15	Each €	> 1
Code C 3266 2000	C 3266/2	Each €	3 1

Refractometers --- H 9 pag. 699

Pullers → C 1 pag. 296



Anti-freeze testers

To determine the freezing point of the anti-freeze and water mixture in motor vehicle radiators - For ethylene glycol based anti-freeze

www.abctools.it

C 3267/0 -Bulb type

With transparent plastic cylinder and aerometer graduated from -40°C to -10°C

C 3267/1 -Traditional cylindrical type

Glass with number scale and graduations

Overall length 350 mm - Ø container 20 mm

C 3267/2 -Simple type

Plastic body - With protected pointer

Graduation -5°C ÷ -40°C

Flexible tube for adapting to openings - Dimensions 155x120 mm

	adapting to openings	DITTOTISIONS TOOKTZO ITIITI		
Code C 3267 0000	C 3267/0	Each €	3	1
Code C 3267 1000	C 3267/1	Each €	3	1
Code C 3267 2000	C 3267/2	Each €	3	1

Special pick-up tools → A 2 pag. 29



Windscreen washer adjusting tool

Telescopic rod with magnetic head Ø 6 mm and point for adjusting the water jet The extracted rod indicates the direction of the water jet on the windscreen With protective cap for the point

Length: closed 150 mm - open 660 mm



