Inspection flashlights

Professional models particularly suited for inspection and maintenance

FABC TOOLS

Polycarbonate body resistant to water

Compact size, with super bright and long lasting LED

With pocket clip and strap with safety hook

Luminous flux 8,9 lm - 0,18 W Beam power: 6000 CP (Candle Power)

Complete with 4 LR 44 coin cells (battery life time approx. 130h)

Overall length 65 mm

	<u> </u>				_
Code A 1	526 7000	A 1526/7	Each €	-	12



Body in anodized aluminium, black painted

With halogen lamp producing a wide, high-intensity beam Internal and external anodizing - Water and shock-resistant Also ideal for use on helmets with light holder clips N 9099/5 Overall length 145 mm - Body diameter 18 mm

Complete with 2 AA 1,5V batteries - In plastic case





FABC TOOLS

FLASH PEN model

Pencil flashlight with 1W CREE XP-G LED Luminous flux 100 Lumen - 300-4000 lux at 0,5 m

Luminous flux max length 75 m

Complete with 2 AAA batteries (approx. operating time 6h) and pocket clip

Body in sturdy, resistant and high quality metal

Metallic grey colour

Dimensions Ø 16 x 148 mm - Weight 56 g 75 m Code N 9097 9300 N 9097/93 Each €



IP

(SCANGRIP'

FLASH 100 model

With 1W CREE XP-G LED with focus function to vary the beam angle from 10° to 70°


Soft rubber-coated body with ergonomic handle Luminous flux 130 Lumen - 800÷12000 lux at 0,5 m

Luminous flux max length 125 m

With 3 1,5V AAA batteries - Approx. operating time 7h Supplied with nylon case with eyelet for attaching to

the belt and wrist strap

Dimensions Ø 32 x 111 mm - Weight 130 g





IP

FLASH 200 model

With 3W CREE XP-G LED with focus function to vary the beam angle from 10° to 70°

Luminous flux 200 Lumen - 800÷22000 lux @ 0,5 m

Luminous flux max length 180 m

With 2 1,5V C batteries

Approx. operating time 3h

Supplied with nylon case with eyelet for attaching to the belt

Dimensions Ø 40 x 165 mm - Weight 238 g

180 m Code N 9097 9700 N 9097/97 Each € **3**





IP 54

FLASH 300 model

With 3W CREE XP-G LED with focus function to vary the beam angle from 10° to 70°

Luminous flux 300 Lumen - 1200÷35000 lux @ 0,5 m

Luminous flux max length 210 m

With 3 1,5V C batteries

Approx. operating time 9h

Supplied with nylon case with eyelet

for attaching to the belt

Dimensions Ø 42x216 mm - Weight 550 g

Code N 9097 9800 N 9097/98





N 8 → pag. 992