

Wheel brushes with hole

Twist knot wire

For heavy-duty applications with high rotational speed - Long lasting and highly resistant to breaking
Ideal for deburring, removing rust, paint, mold, scale and weld seams


With non threaded hole Ø 22,2 mm

D 4015/6 - **ABC TOOLS** - With tempered steel wire Ø 0,50 mm

D 4015/8 - **osborn** - With tempered steel wire Ø 0,50 mm

D 4015/9 - **osborn** - With stainless steel wire Ø 0,50 mm - INOX

Diameter D	mm	115	125	150	178
Code		D 4015 6115	—	D 4015 6150	D 4015 6178
D 4015/6	Each €				
Code		D 4015 8115	D 4015 8125	—	D 4015 8178
D 4015/8	Each €				
Code		D 4015 9115	D 4015 9125	—	D 4015 9178
D 4015/9	Each €				
A face width approx.	mm	12	13	13	13
Wire free lenght T	mm	23	38	37	42
Knots of wire	n°	20	20	24	30
Max speed	rpm	12500	12500	12000	12000



Non threaded hole Ø 22,2 mm



D 4015/6 - 4015/8



D 4015/9 - INOX



D 3



With flexible crimped brass-plated steel wire Ø 0,30 mm - Threaded hole M 14x2

Suitable for roughening surfaces, deburring, descaling, removing mold and enamels and cleaning
Make surfaces smooth and polished

Convex cup to work in hard-to-reach places, on edges and irregular surfaces

Diameter "D" 100 mm - "A" face width approx. 10 mm - Wire free lenght "T" 20 mm

Max speed 10000 rpm

Code D 4016 7100	D 4016/7	Each €	1
------------------	----------	--------	---



Threaded hole M 14x2



Knots of flexible, crimped, brass-plated steel wire Ø 0,27 mm


Threaded hole M 14x2 - Reinforced, high-strength wire

Suitable for roughening surfaces, deburring, descaling, removing mold and enamels and cleaning
Makes surfaces smooth and polished and are ideal for use in hard-to-reach places

Diameter "D" 115 mm - "A" face width approx. 12 mm - Wire free lenght "T" 28 mm

Max speed 12000 rpm

Code D 4017 5115	D 4017/5	Each €	1
------------------	----------	--------	---



Threaded hole M 14x2



Cup brushes with hole

Suitable for roughening surfaces, deburring, descaling, removing mold and enamels and cleaning
Make surfaces smooth and polished and are ideal for use in hard-to-reach places

With non threaded hole Ø 22,2 mm


osborn - With crimped steel wire Ø 0,30 mm

Diameter D	mm	75*	80	100	125	150
Code		D 4019 4075	D 4019 4080	D 4019 4100	D 4019 4125	D 4019 4150
D 4019/4	Each €					
Wire free lenght T	mm	23	25	30	30	40
Max speed	rpm	12500	8500	8500	6500	4500
Suitable on grinders	mm	125	180	180	230	230

* Non threaded hole Ø 16 mm



Non threaded hole Ø 22,2 mm



With threaded hole M 14x2


D 4019/6 - **ABC TOOLS** - With crimped brass-plated steel wire Ø 0,30 mm

D 4019/7 - **osborn** - With crimped steel wire Ø 0,30 mm

D 4019/8 - **osborn** - With crimped stainless steel wire Ø 0,30 mm - INOX

Diameter D	mm	60	75	80	100	125	150
Code	D 4019	6060	6075	6080	6100	6125	6150
D 4019/6	Each €						
Code	D 4019	7060	7075	7080	7100	7125	7150
D 4019/7	Each €						
Code	D 4019	8060	8075	8080	8100	—	—
D 4019/8	Each €						
Wire free lenght T	mm	21	23	25	30	30	40
Max speed	rpm	12500	12500	8500	8500	6500	4500
Suitable on grinders	mm	115	115	180	180	230	230

Threaded hole M 14x2



D 4019/6



D 4019/7



D 4019/8 - INOX

