

Fibre discs

High flexibility, high stock removal and long service life. They are used with a special backing plate on angle grinders - For 80 m/s maximum peripheral speed



Corundum

Suitable for deburring, polishing, grinding and finishing on all surfaces in metal (iron, steel, cast iron, etc.), brass, bronze, wood, plastics, etc.


Version with hole Ø 22 mm - In indivisible pack of 50 pcs.

D 9694/3 - Diameter 115 mm - Rotational speed 13300 rpm

D 9694/7 - Diameter 125 mm - Rotational speed 12300 rpm

D 9694/9 - Diameter 178 mm - Rotational speed 8600 rpm

Grit	16	24	36	46	50	60	80	100	
Code	D 9694	3016	3024	3036	3046	3050	3060	3080	3100
D 9694/3 - Ø 115 mm	Each €								
Code	D 9694	7016	7024	7036	7046	—	7060	7080	7100
D 9694/7 - Ø 125 mm	Each €								
Code	D 9694	9016	9024	9036	9046	9050	9060	9080	9100
D 9694/9 - Ø 178 mm	Each €								




Version with slotted hole Ø 22 mm - In indivisible pack of 25 pcs.

D 9694/2 - Diameter 115 mm - Rotational speed 13300 rpm

D 9694/6 - Diameter 125 mm - Rotational speed 12300 rpm

D 9694/8 - Diameter 178 mm - Rotational speed 8600 rpm

Grit	16	24	36	50	60	80	100	
Code	D 9694	—	2024	2036	2050	2060	2080	2100
D 9694/2 - Ø 115 mm	Each €							
Code	D 9694	—	6024	6036	6050	6060	6080	6100
D 9694/6 - Ø 125 mm	Each €							
Code	D 9694	8016	8024	8036	8050	8060	8080	8100
D 9694/8 - Ø 178 mm	Each €							



Quality EXTRA - Long service life

Zirconia with slotted hole Ø 22 mm


Suitable for removing residues, deburring and grinding all surfaces in metal (iron, steel, cast iron, etc.) and in particular **stainless steel**

In indivisible pack of 25 pcs.

D 9695/1 - Diameter 115 mm - Rotational speed 13300 rpm

D 9695/3 - Diameter 178 mm - Rotational speed 8600 rpm

Grit	36	50	60	80
Code	D 9695 1036	D 9695 1050	D 9695 1060	D 9695 1080
D 9695/1 - Ø 115 mm	Each €			
Code	D 9695 3036	D 9695 3050	D 9695 3060	—
D 9695/3 - Ø 178 mm	Each €			



Fibre discs for orbital sanders

In corundum abrasive paper

With **Velcro backing** for fastening to backing plates coated with hook-and-loop fabric similar to «Velcro»
High material removal on metal, wood and plastic surfaces for paints, plaster, etc.

In indivisible pack of 50 pcs.


With hole design for improved dust extraction

D 9695/5 - Diameter 125 mm - 8-hole configuration - Rotational speed 12300 rpm

D 9695/6 - Diameter 150 mm - 7-hole configuration - Rotational speed 10200 rpm

D 9695/7 - Diameter 150 mm - 9-hole configuration - Rotational speed 10200 rpm

Grit	40	60	80	100	120	
Code	D 9695	5040	5060	5080	5100	5120
D 9695/5 - Ø 125 mm	Each €					
Code	D 9695	6040	6060	6080	6100	—
D 9695/6 - Ø 150 mm	Each €					
Code	D 9695	7040	7060	7080	7100	—
D 9695/7 - Ø 150 mm	Each €					



D 9695/5



D 9695/7

No hole configuration

D 9695/8 - Diameter 115 mm - Rotational speed 13300 rpm

D 9695/9 - Diameter 150 mm - Rotational speed 10200 rpm

Grit	40	60	80	120	
Code	D 9695	8040	8060	8080	8120*
D 9695/8 - Ø 115 mm	Each €				
Code	D 9695	9040	9060	9080	—
D 9695/9 - Ø 150 mm	Each €				

