

ABC TOOLS Keyed chucks

With 3 jaws - Steel body, tempered jaws

Light type for portable rotation and hammer impact drills

With threaded pin - $\frac{3}{8}$ " x 24 UNF

For drills up to Ø	mm	10	13
Code		E 1120 8010	E 1120 8013
E 1120/8	Each €		
Minimum opening	mm	0,5	1,5

E 1120/9 - With threaded attachment - $\frac{3}{8}$ " x 24 UNF - For reversible drills

E 1120/11 - With threaded attachment - $\frac{1}{2}$ " x 20 UNF - For reversible drills

E 1120/12 - With threaded attachment - $\frac{5}{8}$ " x 16 UNF

For drills up to Ø	mm	10	13	16
Code		E 1120 9010	—	—
E 1120/9	Each €			
Code		E 1120 1110	E 1120 1113	E 1120 1116
E 1120/11	Each €			
Code		—	—	E 1120 1216
E 1120/12	Each €			
Minimum opening	mm	1,5	1,5	3,0



Threaded pin



Threaded attachment

Heavy type for column and radial drills, lathes and milling machines

With conical attachment DIN 238/2 (For attachments see G 900/1 - G 900/2)

Standard version

For drills up to Ø	mm	10	13	16
Code		E 1121 0010	E 1121 0013	E 1121 0016
E 1121/0	Each €			
Minimum opening	mm	0,5	1,5	2,5
Attachment DIN 238/2		B 12	B 16	B 16



Conical attachment DIN 238/2

Spare key - For chucks E 1120/8 ÷ E 1121/4

Size	10	13	13	16
Code	E 1121 3010	E 1121 3013	E 1121 3131	E 1121 3016
E 1121/3	Each €			
Suitable for chucks	E 1120/8 sz. 10 E 1120/9 sz. 10 E 1120/11 sz. 10	E 1120/11 sz. 13 E 1121/0 sz. 10 E 1121/0 sz. 13	E 1120/8 sz. 13	E 1120/12 sz. 16 E 1121/0 sz. 16 E 1121/4



Industrial and precision version

For drills up to Ø	mm	13	16
Code		E 1121 4013	E 1121 4161
E 1121/4	Each €		
Minimum opening	mm	0	3
Attachment DIN 238/2		B 16	B 18

ABC TOOLS Keyless chucks

With 3 jaws - Steel body

Suitable for cordless and electric drills

Reversible for right and left rotation - Manual lock through body rotation

Type with thermoresin coated body

For drills up to Ø	mm	10	10	13
Code		E 1121 7010	E 1121 7011	E 1121 7013
E 1121/7	Each €			
Minimum opening	mm	0,8	1,5	1,5
Threaded attachment		$\frac{3}{8}$ " x 24 UNF	$\frac{3}{8}$ " x 24 UNF	$\frac{1}{2}$ " x 20 UNF
Length closed	mm	54	54	62,5
External diameter	mm	43	43	45



Threaded attachment

Type with fast and safe tightening, suitable for working safely, also in case of strong vibrations

Suitable also for hammer impact drills with power from 800W to 1200W

Hard metal jaws for a better locking of the drill and a longer duration

For drills up to Ø	mm	13
Code		E 1121 7513
E 1121/75	Each €	
Minimum opening	mm	2
Threaded attachment		$\frac{1}{2}$ " x 20 UNF
Length closed	mm	67
External diameter	mm	42,5

Hard metal jaws



Threaded attachment