

## Compressed air hose reels

**ABC TOOLS**

Frame in galvanized, polished steel tube

Reel in thermoplastic resin, resistant to breaking

**With flexible and strong crystal PVC hose**, resistant to oil and with quick brass connectors

Axial connection for hose winding and unwinding during use

The compressed air flows through the steel tube which works also as a support for hanging it to the wall

**Hose length 20 m - internal Ø 9 mm - external Ø 15 mm - Working pressure 15 bar**

Code E 1143 2000	<b>E 1143/2</b>	Each €	 1
------------------	-----------------	--------	---

IP  
44



**HOELOCK**

Polypropylene support, resistant to breaking

**With spring mechanism and hose guide** for unwinding and blocking the hose according to the length desired and for winding rapidly without twisting the hose

With **180° orientable bracket**, to reach every working area

**With 10 m hose SUPER NOBELAIR® SOFT model**, with internal Ø 8 mm and hose with tap connection 1,5 m

Working pressure 10 bar - Burst pressure 40 bar - With brass coupling 1/4" BSP

Support dimensions LxDxh 420x170x335 mm - Weight (everything included) 4 kg

Code E 1143 5000	<b>E 1143/5</b>	Each €	 1
------------------	-----------------	--------	---

**With 20 m hose TECHNOBEL® PU model**, with internal Ø 9,5 mm and hose with tap connection 2 m

**Hose with four layer structure:** outside in black extra-flexible PVC resistant to hydrocarbon, polyester fiber interwoven reinforce and inside in PVC and transparent polyurethane

High resistance to oils, hydrocarbons and several types of solvents

Working pressure 10 bar - Burst pressure 40 bar - With brass coupling 1/4" BSP

Support dimensions LxDxh 484x268x428 mm - Weight (everything included) 8 kg

Code E 1143 7000	<b>E 1143/7</b>	Each €	 1
------------------	-----------------	--------	---



## **HAZET** Special oil for pneumatic tools

Suitable for mechanic-operated pneumatic tools (for ex. impact wrenches, grinders)

**Without silicone**

It reduces motor wear and extends the tool life if used on a regular basis

The size 100 with spout for direct application

Contents	ml	100	1000
Code		<b>E 1144 1100</b>	<b>E 1144 1990</b>
<b>E 1144/1</b>	Each €		



100 ml

1000 ml

## **HAZET** Mini-oiler for pneumatic tools

**For automatic lubrication of pneumatic tools**

**Refillable, capacity 28 ml - Air inlet attachment 1/4"**

Brass body with plastic container

Compact, to be fixed directly to the tool

Suitable for most of the pneumatic tools, and it ensures longer tool life

Code E 1144 5028	<b>E 1144/5</b>	Each €	 1
------------------	-----------------	--------	---



## **ABC TOOLS** Thermoplastic oiler

Type with brass pipe and resin head

With fixed tube

Capacity	ml	125	170	300	500
Code		<b>K 3914 0125</b>	<b>K 3914 0170</b>	<b>K 3914 0300</b>	<b>K 3914 0500</b>
<b>K 3914</b>	Each €				



## Hose clips – non perforated band


**Ace** - Conforming to DIN 3017 standard

**Entirely in galvanized steel** - Mod. NP9 - W1

With non-perforated band, length 9 mm and rounded edges

High-resistance and it can be used several times - High clamping with low tightening torque

Hex head 7 mm - Clamping

For hoses with	Ø mm	8÷12	10÷16	12÷22
Code		<b>L 6570 1008</b>	<b>L 6570 1010</b>	<b>L 6570 1012</b>
<b>L 6570/1</b>	Each €			
	Pcs	50	50	50



Band width 9 mm