


Twist drills with Morse taper shank

continuation



HSS	DIN 345	Type N	RH	118°	h 8
-----	---------	--------	----	------	-----

Ø mm	Code F 7558 ...	F 7558 Each €	Code F 7560	F 7560 Each €	CM	L1 mm	L2 mm	Ø mm	Code F 7558 ...	F 7558 Each €	Code F 7560 ...	F 7560 Each €	CM	L1 mm	L2 mm	Ø mm	Code F 7560	F 7560 Each €	CM	L1 mm	L2 mm
38,50	—		3850		4	349	200	48,00	4800		4800		4	369	220	63,00	6300		5	427	240
39,00	3900		3900		4	349	200	48,50	—		4850		4	369	220	65,00	6500		5	432	245
39,50	—		3950		4	349	200	49,00	4900		4900		4	369	220	70,00	7000		5	437	250
40,00	4000		4000		4	349	200	49,50	—		4950		4	369	220	71,00	7100		5	437	250
40,50	—		4050		4	354	205	50,00	5000		5000		4	369	220	72,00	7200		5	442	255
41,00	4100		4100		4	354	205	51,00	5100		5100		5	412	225	73,00	7300		5	442	255
41,50	—		4150		4	344	205	52,00	5200		5200		5	412	225	77,00	7700		6	514	260
42,00	4200		4200		4	354	205	53,00	—		5300		5	412	225	78,00	7800		6	514	260
42,50	—		4250		4	354	205	54,00	5400		5400		5	417	230	79,00	7900		6	514	260
43,00	4300		4300		4	359	210	55,00	5500		5500		5	417	230	82,00	8200		6	519	265
44,00	4400		4400		4	359	210	56,00	—		5600		5	417	230	83,00	8300		6	519	265
45,00	4500		4500		4	359	210	57,00	—		5700		5	422	235	84,00	8400		6	519	265
45,50	—		4550		4	364	215	58,00	5800		5800		5	422	235	85,00	8500		6	519	265
46,00	4600		4600		4	364	215	59,00	—		5900		5	422	235	90,00	9000		6	524	270
46,50	—		4650		4	364	215	60,00	6000		6000		5	422	235	95,00	9500		6	529	275
47,00	4700		4700		4	364	215	61,00	—		6100		5	427	240						

1 pce.

NORMEX® Extra long twist drills with Morse taper shank

HSS	DIN 1870	Type N	RH	118°	h 8	A shape
-----	----------	--------	----	------	-----	---------



Ø mm	Code	F 7564/1 Each €	CM	L1 mm	L2 mm	Ø mm	Code	F 7564/1 Each €	CM	L1 mm	L2 mm	Ø mm	Code	F 7564/1 Each €	CM	L1 mm	L2 mm
8	F 7564 1008		1	265	165	15	F 7564 1015		2	340	220	22	F 7564 1022		2	405	270
9	F 7564 1009		1	275	175	16	F 7564 1016		2	355	230	23	F 7564 1023		2	405	270
10	F 7564 1010		1	285	185	17	F 7564 1017		2	355	230	24	F 7564 1024		3	440	290
11	F 7564 1011		1	300	195	18	F 7564 1018		2	370	245	25	F 7564 1025		3	440	290
12	F 7564 1012		1	310	205	19	F 7564 1019		2	370	245	26	F 7564 1026		3	440	290
13	F 7564 1013		1	310	205	20	F 7564 1020		2	385	260						
14	F 7564 1014		1	325	220	21	F 7564 1021		2	385	260						

1 pce.



Ø mm	Code	F 7564/3 Each €	CM	L1 mm	L2 mm	Ø mm	Code	F 7564/3 Each €	CM	L1 mm	L2 mm	Ø mm	Code	F 7564/3 Each €	CM	L1 mm	L2 mm
8	F 7564 3008		1	330	210	15	F 7564 3015		2	425	275	21	F 7564 3021		2	490	325
9	F 7564 3009		1	345	220	15,5	F 7564 3155		2	445	295	21,5	F 7564 3215		2	515	345
10	F 7564 3010		1	360	245	16	F 7564 3016		2	445	295	22	F 7564 3022		2	515	345
10,5	F 7564 3105		1	360	235	16,5	F 7564 3165		2	445	295	23	F 7564 3023		2	515	345
11	F 7564 3011		1	375	250	17	F 7564 3017		2	445	295	24	F 7564 3024		3	555	365
11,5	F 7564 3115		1	375	250	17,5	F 7564 3175		2	465	310	25	F 7564 3025		3	555	365
12	F 7564 3012		1	395	260	18	F 7564 3018		2	465	310	26	F 7564 3026		3	555	365
12,5	F 7564 3125		1	395	260	18,5	F 7564 3185		2	465	310	27	F 7564 3027		3	580	385
13	F 7564 3013		1	395	260	19	F 7564 3019		2	465	310	28	F 7564 3028		3	580	385
13,5	F 7564 3135		1	410	275	19,5	F 7564 3195		2	490	325	29	F 7564 3029		3	580	385
14	F 7564 3014		1	410	275	20	F 7564 3020		2	490	325	30	F 7564 3030		3	580	385
14,5	F 7564 3145		2	425	275	20,5	F 7564 3205		2	490	325						

1 pce.