


felo Torque screwdrivers with interchangeable blades

System consisting of interchangeable blades to be used with the handle for adjusting the torque value
Recharges automatically, for right-hand use
Accuracy $\pm 6\%$ of all values

Micrometer torque can be adjusted by rotating the screw on top of the handle with a hex key
L-wrench (supplied)

It makes a click sound when the preset value is reached
Particularly suited for tightening screws on carbide inserts



Torque setting



Blade for inserts



VDE blades

Interchangeable blades, in chrome-molybdenum-vanadium steel

Overall length 170 mm

A 2828/1 - Non coated blade

A 2828/11 - VDE slim, blade insulation up to 50% thinner, ideal for reaching deep screws

Size	3,0x0,5	3,5x0,6	4,0x0,8	5,5x1,0	PH0	PH1	PH2	PZ0	PZ1	PZ2	T6	T7
Code	A 2828 1003	1005	1006	1007	1013	1014	1016	1018	1019	1021	1023	1024
A 2828/1 Each €												
Code	A 2828 —	1105	1106	1107	—	1114	1116	—	1119	1121	—	—
A 2828/11 Each €												
Max tightening capacity Nm	1,5	1,5	3	3	1,5	3	5,4	1,5	3	5,4	1,5	1,5
Size	T8	T9	T10	T15	T20	T25	IP6	IP7	IP8	IP9	IP10	IP15
Code	A 2828 1025	1026	1027	1028	1029	1030	1051	1052	1053	1054	1055	1056
A 2828/1 Each €												
Size	IP20	IP25	H1	H2	Z1	Z2	1/4"	1,5 mm	2 mm	2,5 mm	3 mm	4 mm
Code	A 2828 1057	1058	1064	1065	1066	1067	1071	1081	1082	1083	1084	1085
A 2828/1 Each €												
Code	A 2828 —	—	—	1165	1166	1167	—	—	—	—	—	—
A 2828/11 Each €												
Max tightening capacity Nm	5,4	5,4	3	3	3	5,4	5,4	1,5	1,5	3	5,4	5,4

Ergonomic handle, in shock-resistant synthetic resin with non-slip soft elastomer coating

for comfortable, safe grip

With colored finger ring for quick identification of the tightening capacity

Overall length 105 mm

Tightening capacity Nm	0,6 ÷ 1,5	1,5 ÷ 3	3 ÷ 5,4
Code	A 2828 2015	A 2828 2003	A 2828 2054
A 2828/2 Each €			
Scala con graduazione Nm	0,1	0,1	0,2
Graduated scale Nm	0,1	0,1	0,2



1,5 Nm



3 Nm



5,4 Nm

Insert to avoid torque misadjustment for handles A 2828/2

Code A 2828 3000	A 2828/3	Each €	1
-------------------------	-----------------	--------	---

Torque screwdrivers complete with blade, consisting of:

1 handle A 2828/2

1 interchangeable blade with 1/4" drive bit holder A 2828/1 sz. 71

Tightening capacity Nm	0,6 ÷ 1,5	1,5 ÷ 3	3 ÷ 5,4
Code	A 2828 5015	A 2828 5003	A 2828 5054
A 2828/5 Each €			
Graduated scale Nm	0,1	0,1	0,2



Hex L-wrench with 6 mm, suitable for adjustment torque

Code A 3106 1006	A 3106/1	Each €	25
-------------------------	-----------------	--------	----

A 8 → pag. 94

Screwdriver bits → A 5 pag. 37

Bit holder sockets → A 5 pag. 45

Sets of interchangeable blades, consisting of:

1 handle A 2828/2

12 interchangeable blades as described in the table

In painted metal box, dimensions 220x110x35h mm - Weight 1 kg

Tightening capacity Nm	0,6 ÷ 1,5	1,5 ÷ 3	3 ÷ 5,4
Code	A 2828 0015	A 2828 0003	A 2828 0054
A 2828 Each €			
Graduated scale Nm	0,1	0,1	0,2
Complete with blades:	<ul style="list-style-type: none"> 3x0,5 - 3,5x0,6 PH0 PZ0 T6 - T7 - T8 IP6 - IP7 - IP8 - IP9 bit holder 1/4" 	<ul style="list-style-type: none"> 4x0,8 PH1 - PH2 PZ1 - PZ2 T9 - T10 - T15 IP9 - IP10 - IP15 bit holder 1/4" 	<ul style="list-style-type: none"> 4x0,8 PH1 - PH2 PZ1 - PZ2 T15 - T20 - T25 IP9 - IP10 - IP15 bit holder 1/4"

1/4" 1/4"

