## Measuring tapes in capsules

Manufactured according to 2014/32/EV European directives «A» version: graduation starts after 10 cm from the steel terminal ring With shockproof synthetic resin case with "soft-touch" surfaces for easy grip The crank can be fixed on both sides for left-hand users

#### Type fiberglass tape

Black cm graduation on one side - Class II (±2,3 mm/10 m) aduated


The first 10 cm are millimeter	gra

Red number at every meter

Meter repetition at every decimeter				00	
Tape length	m	10	20	30	
Code		H 5109 0010	H 5109 0020	H 5109 0030	
H 5109	Each €				
Tape width	mm	13	13	13	

### Black cm graduation on both sides - Class III (±4,6 mm/10 m)

Red number at every meter Meter repetition at every decimeter		↓     D 60   /		
Tape length	m	10	20	30
Code		H 5111 0010	H 5111 0020	H 5111 0030
H 5111	Each €			
Tape width	mm	13	13	13



# 10 cm «A» version: graduation starts after 10 cm from the steel terminal ring Reversible crank



#### Type with enamelled steel tape white - Class II (±2,3 mm/10 m)

#### Black mm graduation on one side

Red number at e Meter repetition a With wrist band	,	meter	55 56 57 58 59 🛄 60 61 62 63
Tape length	m	10	20
Code		H 5115 0010	H 5115 0020
H 5115	Each €		
Tape width	mm	10	10

#### Black mm graduation on one side

With flexible coating «FLEXTOP» (patented) on the initial part of the tape to ensure long durability

Red number at every meter
Meter repetition at every decimete

Red number at ev	very meter			
Meter repetition at every decimeter		55 56 57 56	59 0 60 61 62 63 64 65	
Tape length	m	10	20	50
Code		H 5120 2010	H 5120 2020	H 5120 2050
H 5120/2	Each €			
Tape width	mm	13	13	13

Type with coated steel tape «ISOLAN» - Class II (±2,3 mm/10 m)

Polyamide coating with anti-wear protection, resistant to acids, oils, fats etc. Lighter tape compared to common and traditional steel - Breaking resistance R 170 kg/mm<sup>2</sup>

#### Black mm graduation on one side

With flexible coating «FLEXTOP» (patented) on the initial part of

the tape to ensure long durability

Red number at e	very meter		
Meter repetition at every decimeter			54 55 56 57 58 59 46061 62 63 64 6
Tape length	m	20	30
Code		H 5121 0020	H 5121 0030
H 5121	Each €		
Tape width	mm	13	13
			*



tor

#### Type with stainless steel tape gray - Class II (±2,3 mm/10 m)

#### Polished mm graduation on one side

With flexible coating «FLEXTOP» (patented) on the initial part of the tape to ensure long durability Numbers at every meter

Trainiboro at oron	,		
Meter repetition at every decimeter			55 56 57 58 59 0 60 61 62 63 64 65
Tape length	m	20	50
Code		H 5122 0020	H 5122 0050
H 5122	Each €		



