Entirely in forged steel with sliding front jaw

Tempered steel manoeuvring screw, highly protected against dust, dirt infiltrations.

The vice slender body allows for the lateral clamping of vertical workpieces

The **pipe jaws** are obtained from the body

## Model «HEUER FRONT»

Jaws and body in a single piece - Double ground and prismatic rail with adjustment screws L 3372/0 - With interchangeable jaws with screw (with one knurled and one smooth face)

L 33/2/1 - With fixed jaws						
Jaw width	mm	100	120	140	160	180
Code		_	L 3372 0120	L 3372 0140	L 3372 0160	_
L 3372/0	Each €					
Code		L 3372 1100	L 3372 1120	L 3372 1140	L 3372 1160	L 3372 1180
L 3372/1	Each €					
Maximum opening	mm	125	150	200	225	225
Total height	mm	124	156	192	225	225
Depth	mm	50	65	80	100	100
Jaws for pipes	inches	3/8 ÷ 1 3/16	5⁄8 ÷ 2 3⁄16	1 ½16 ÷ 2 ¾	1 ½16 ÷ 4	1 ½16 ÷ 4
Weight approx.	kg	4,5	9	16	27	29





Model «HEUER Compact» - Quick opening

With "Quicklaunch" system which allows the jaws span width to be adjusted from 0 to 130 mm without using the operating lever Body with scale in centimetres for the pre-adjustment of the span

width, which once it is obtained can be heard and seen Lean and light body with clamping force 10 kN

With interchangeable jaws with screw (with one knurled surface and one smooth surface)

Jaws length 120 mm - Max span width 130 mm

With jaws for pipes Ø 5/8" - 2"

Total height 156 mm - Depth 65 mm - Weight 4.5 kg

Total Holgitt Too Hill	Boptil oo min vvoignt i,	,e ng		_
Code L 3377 0120	L 3377	Each <b>€</b>	<b>3</b> 1	



## L 3373 -Tempered steel jaws for vices L 3372/0 and L 3377

Designed for screw fastening - Reversible, with one knurled surface and one smooth surface

. **3374 - Swivel base** for vices L 3372/0 - L 3372/1 and L 3377

L 33/4 -3Wivei base for vices L 33/2/0 - L 33/2/1 and L 33/1				
Size	100	120	140	160
Code	_	L 3373 0120	L 3373 0140	L 3373 0160
<b>L 3373</b> Per pair €				
Code	L 3374 0100	L 3374 0120	L 3374 0140	L 3374 0160*
L 3374 Each €				



Suitable for vices L 3372/1 of 100 mm and L 3377 - Clamp opening 65 mm

Code L 3376 1000	L 3376/1	Each €	<b>3</b> 1

## Orientable supports for vices L 3372/0 - L 3372/1

For workbenches with wooden surface (see group N 3)

Stable and safe vice fixing, anti-vibrations

Forged base plate - Milled supporting and contact plate

## 2-functions type

1) Rotating base - 2) Vice raises and lowers

With pneumatic pressure shock absorber to balance the weight

360° rotating vice - Height-adjustable max. 200 mm - Weight 9 kg

For vices	mm	120	140	160
Code		L 3376 2120	L 3376 2140	L 3376 2160
L 3376/2	Each €	·		
Allowable load	kg	4÷10	10÷16	16÷29

3-functions type

1 Rotating base - 2 Vice raises and lowers - 3 Tipping under work surface

With 2 telescopic shock absorbers for tipping the support and pressure pneumatic shock absorber to balance the weight

\*\*Light adjustable max. 180 mm - Weight 14 kg

rotating vice - Height-adjustable max. 180 mm - Weight 14 kg				
For vices mm		120	140	
Code		L 3376 3120	L 3376 3140	
L 3376/3	Each €			
Allowable load	kg	4÷10	10÷16	

Warning: for safety reasons it is recommended to tip the vice once it is fixed














Workbenches with wood countertop → N 3 pag. 935