FN 358

Usable with harnesses M 3464/3 and M 3464/6

#### With 3 steel "D" rings and continuous adjustment buckle

Load-bearing band in polyester, width 45 mm

Polyamide thread strap, high strength

Comfortable back support, ergonomic and padded with special foam

Back support height 200 mm

Pelvis circumference 90÷120 mm

Code M 3464 1002 M 3464/1

Each €





## Fall prevention harnesses

# **Type with 1 rear connector** EN 361

Seams in high-tenacity polyamide thread Locking thigh-strap buckles in galvanized steel Adjustable polyamide straps, width 44 mm

Circumference: chest 75÷150 cm - thigh 60÷85 cm Torso height 55÷85 cm

Code M 3464 3000

M 3464/3

Each €



### Type with 1 rear connector and positioning belt

EN 358 - EN 361

Seams in high tenacity polyamide thread

Galvanised steel wedge buckles for thigh straps

Adjustable polyamide buckles, width 44 mm Circumference: chest 75÷150 cm - thigh 60÷85 cm

Upper body height 65÷85 cm

Belt with two steel side "D" rings and buckle with

continuous adjustment

Ergonomic and comfortable, foam-padded back

Back height 200 mm

Pelvis circumference 90÷120 mm

Code M 3464 4000

M 3464/4

Each €





### Type with 1 front connector at the chest and 1 at the back

EN 361

One size

Can be combined with belt M 3464/1

Stitching in high strength polyamide thread

Galvanised steel wedge buckle for thigh protectors

Adjustable polyamide straps, width 44 mm


Circumference: chest 80÷140 cm - thigh 65÷75 cm

Upper body brace height 65÷85 cm

Code M 3464 6000

M 3464/6

Fach €



## "Comfort" type with 1 front connector at the chest and 1 on the back

Reinforced model with ergonomic back, shoulder and thighs to improve comfort while working and after a fall

Reduces the effects of inert suspension

With slots for fixing brackets for preventing suspension syndrome

Stitching in high strength polyamide thread

Adjustable polyamide straps, width 44 mm

Circumference: chest 80÷140 cm - thigh 75÷100 cm

Upper body brace height 65÷95 cm

Code M 3464 7000

M 3464/7

Each €





With manual adjuster - EN 358

Usable with all harnesses and belts

Length adjustable from 1,15÷2 m

Polyamide fibre rope 10,5 mm Ø and oval steel connector

With 2 carabiners in galvanized steel with ring nut lock

Clear passage 16 mm Ø

Manual aluminium alloy ring adjuster that obliges the user to use both hands to

adjust the rope when it is not tensioned

Code M 3466 2000

M 3466/2



