

KNIPEX "StriX" wire stripper plier with wire shear

In special, forged, oil-hardened steel - DIN ISO 5749
 Suitable for single-pole, multi-wire, thin wire conductors with synthetic resin or rubber insulation with max Ø 5 mm and cross section 10 mm²
 Slim head shape to easily reach the workpiece
 With induction hardened and precision ground cutting edge **to cut copper and aluminium wires up to Ø 15 mm (50 mm²)** without the risk of crushing
 Manual adjustment by contrasting screw
 Handles coated in two-component material - Clean head
 Overall length 180 mm

Code M 7138 2300	M 7138/23	Each €		6
-------------------------	------------------	--------	---	---



KNIPEX Crimper for ferrules

For **crimping terminals with a cross section of 0,25÷16 mm²** (AWG 23-5) to DIN 46228 standard (1+4) - **In special forged, oil tempered steel**
 Two-component thick handles with hand guard - With 9 settings
 Overall length 180 mm



Code M 7139 0300	M 7139/03	Each €		1
-------------------------	------------------	--------	---	---



KNIPEX Water pump plier - Cobra®

In chrome-vanadium steel, forged and oil-hardened - DIN ISO 8976
 With passing hinge with dual guide for high stability and a stopper lever on the handles
 Combined jaws with concave teeth and straight knurling
 Self-locking, no sliding on the workpiece itself, and minimum use of force
 HRc 61 hardened teeth, wear resistant, that always provide a safe grip
Automatic opening adjustment on the workpiece itself, push-button operated
With 24 possible opening settings

For pipes with 2" (50 mm) max Ø - For max 46 mm nuts - Overall length 250 mm

Code M 7142 0325	M 7142/03	Each €		1
-------------------------	------------------	--------	---	---



KNIPEX Cable shear

In special forged, oil-hardened steel - Chromed version
 Hardened and precision-ground blades - With stopper latch
 Insulating handles in two-component plastic material, with hand guard
 For clean, precise, one-handed and deformation-free cutting of single pole and multi-wire copper and aluminium wires

For aluminium or copper electrical wires with cross section up to 50 mm²

Maximum wire opening Ø 15 mm
 Overall length 165 mm - Weight 260 g

Not suitable for cold drawn steel wire and copper cables

Code M 7150 2300	M 7150/23	Each €		6
-------------------------	------------------	--------	---	---



Electric cables



Elastic cords for tying down tools

To withhold tools and protect against the risk of injury and material damage caused by falling
 Suitable for use in construction, roofing, climbing workers, trade fair installation workers, climbers, rock climbers

Flexible anchoring cable to work comfortably and safely
 Outside in embossed fabric band, inside in high-resistance extendible nylon band
NOT certified to secure people




Easy to use: feed the end ribbon through the safety loop in the tool and tighten making it pass through the two steel rings

Max. load 3 kg (tool weight) - **Elongation under load up to about 1,2 m**

M 3465/5 - Fabric loop end, for use with steep carabiner (see grp. L 0)

M 3465/7 - End with carabiner with spring lever


Code M 3465 5000	M 3465/5	Each €		1
-------------------------	-----------------	--------	---	---

Code M 3465 7000	M 3465/7	Each €		1
-------------------------	-----------------	--------	---	---



With loop in flat strip fastened to one side and cord sewn with cord stopper on the other
 Easy to use: insert the cord stopper in the tool's safety loop, thread the entire cord through, pull and lock in place with the cord stops

Also suitable for use with KNIPEX screw drivers tested to VDE standards, using their through-hole
Maximum load 1,5 Kg (tool weight) - **Elongation under load up to about 1,5 m**

Code M 3465 9000	M 3465/9	Each €		1
-------------------------	-----------------	--------	---	---



Use with VDE KNIPEX screwdrivers

