## Ace) Hose clips – non perforated band

Entirely in stainless steel AISI 316L - Compliant with standards DIN 3017

With smooth band and rounded edges for excellent closing without damaging the pipe

Suitable for the maritime sector, petrochemical sector, and food sector

**Sold exclusively in complete** packs (see note at the end of the table)

Type with band width 9 mm - Mod. NPSS9M - W5

Screws with hexagonal head 7 mm - Tightening torque 4.5 Nm

COLCANO MILITIONA	goriai ricaa	i iiiiii iigiit	orming torque	T.O I WITT				
For hoses with	Ø mm	8÷12	10÷16	12÷22	16÷27	20÷32	23÷35	25÷40
Code	L 6576	1008	1010	1012	1016	1020	1023	1025
L 6576/1	Each €							
For hoses with	Ø mm	30÷45	32÷50	40÷60	50÷70	60÷80	70÷90	80÷100
Code	L 6576	1030	1032	1040	1050	1060	1070	1080
L 6576/1	Fach <b>€</b>							





😝 50 pcs. up to Ø 23-35 - 25 pcs. from Ø 25-40 to Ø 40-60 - 20 pcs. Ø 50-70 and Ø 60-80 - 10 pcs. from Ø 70-90 to Ø 120-140

Type with band width 12 mm - Mod. NPSS12M - W5

Screws with hexagonal head 7 mm - Tightening torque 5 Nm

For hoses with	Ø mm	16÷27	20÷32	23÷35	25÷40	30÷45	32÷50	40÷60	50÷70	60÷80	70÷90	80÷100
Code	L 6576	2016	2020	2023	2025	2030	2032	2040	2050	2060	2070	2080
L 6576/2	Each €											
Cay bases with	~							450 450	400 400			
For hoses with	ø mm	90÷110	100÷120	110÷130	120÷140	130÷150	140÷160	150÷170	160÷180	170÷190	180÷200	
Code	Ø mm <i>L 6576</i>	90÷110 2090	100÷120 2100	110÷130 2110	120÷140 2120	130÷150 2130	140÷160 <i>2140</i>	150÷1 <i>7</i> 0 <i>2150</i>	160÷180 <i>2160</i>	170÷190 <i>2170</i>	180÷200 <i>2180</i>	

Band width 12 mm



🝅 10 pcs.



## Ace) Perforated hose clamps

**Entirely in stainless steel AISI 304** 

Suitable for corrosive and humid environments (ship yards, food sector, etc.), automotive sector, industries, etc.

With rounded edges for excellent closing without damaging the pipe

High resistance, and reusable - High grip with low tightening torque

Sold exclusively in a pack of 25 pcs.

Type with band width 8 mm - Mod. PSS8 - W4

Screws with hexagonal head 6 mm - Tightening torque 2.8 Nm

0010110 111011010				10.900 =							
For hoses with	Ø mm	8÷12	10÷16	14÷24	18÷28	24÷36	25÷45	32÷52	40÷60	47÷67	62÷82
Code	L 6580	1008	1010	1014	1018	1024	1025	1032	1040	1047	1062
L 6580/1	Each €										

**<sup>→</sup>** 50 pcs.

Band width 8 mm



Band width 13 mm



Type with band width 13 mm - Mod. PSS13 - W4

Tightening torque 5 Nm (4 Nm up to (2 18:28 mm)

Screws with nexagonal nead 6 mm - highlenling torque 3 mm (4 mm up to 20 fo-26 mm)									
For hoses with	Ø mm	14÷22	18÷28	24÷36	25÷45	32÷52	40÷60	47÷67	
Code	L 6580	2014	2018	2024	2025	2032	2040	2047	
L 6580/2	Each €								
For hoses with	Ø mm	62÷82	77÷97	92÷112	107÷127	122÷142	137÷157		
Code	L 6580	2062	2077	2092	2107	2122	2137		
L 6580/2	Each €								

*Other stainless steel bands* → L 7 pag. 776

## **Martor** Food industry cutter - Accident prevention

Mod. SECUNORM HANDY MDP

Stainless steel body with plastic parts, detectable with metal detector

With side nut, for right of left-handed use and automatically retractable blade

Suitable for the food industry and pharmaceutical industry, and for cutting double corrugated cardboard, film, adhesive tape, and plastic straps

Complete with stainless steel blade M 7070/5, two cutting edges, suitable for contact with food - Blade protrusion 13 mm - Cutting depth 9 mm - Total length 100 mm

**>** 10

M 7070/2 Code M 7070 2000

Spare stainless steel blade, suitable for contact with foodstuffs 4-times usable blade - Suitable for M 7070/2 and M 7070/3  $\,$ 

0,30 mm thick - In pack of 10 blades





