

ABC TOOLS Trolleys/tool cases for technical assistance

For repair technicians, sets of samples, etc. - Tools not provided

Type in shockproof ABS with telescoping frame and 2 wheels Ø 60 mm with aluminium closing profile
 Extractable pulling handle in aluminium alloy, unlockable using the designated button
Complete with 2 ABS tool panels with passing elastics, document pocket and tool pocket
 Design with rounded corners
 Upper panel with holding band, back of the panel made especially for holding wrenches (like N 2280 on page 866)
 Heat-shaped tool holder bottom with movable divisions
 Ergonomic carry handle with soft rubber insert
 Built-in feet obtained from the structure
 Key-operated double-catch **"TSA"* lock**
 Dimensions LxDxh 515x440x255 mm
 Weight 6,6 Kg

| | | | |
|------------------|-----------------|--------|---|
| Code N 2283 3000 | N 2283/3 | Each € |  1 |
|------------------|-----------------|--------|---|



Type entirely in shockproof polyethylene, high density, double wall: characteristics that ensure a high resistance to shocks, extreme weather and temperature conditions, to acids and other chemical agents

Embedded telescoping frame protected with 2 wheels Ø 100 mm
 High stability during transport through big wheels on ball bearings
 Handle for dragging, releasable through button, with soft rubber insert and return spring
With 2 plastic-coated tool panels with elastic bands and pockets for documents with high holding capacity
 Upper panel with extra-long holding belt
 Tool bottom **with adjustable and removable dividers** with 2 removable plastic pouches for small parts
 Embedded feet which are part of the structure itself
Double snap "TSA"* lock with key
 Dimensions 450x345x185h mm
 Weight 7,5 kg

| | | | |
|------------------|-----------------|--------|---|
| Code N 2283 5000 | N 2283/5 | Each € |  1 |
|------------------|-----------------|--------|---|

* **TSA: international mandatory lock system for travelling to and from the United States**
 Authorities can open TSA locks during check-in with no need to reveal the combination, as a master key is used to open the luggage for routine checks



Waterproof cases

In impact resistant synthetic resin
 Ideal for industrial, military, nautical, photography applications, etc.

A valve makes it airtight and dust-proof
 Completely water-proof

Lower compartment with pre-cut cubed foam inlay for easy customisation to fit delicate tools
 Lid padded with foam cones
 With non-slip ergonomic handle and snap clasps
 Reinforced hinges and corners
 Metal inserts in stainless steel
 With 2 holes for padlock attachment



Case type

| Width | mm | 330 | 430 | 515 |
|---------------------|--------|-------------|-------------|-------------|
| Code | | N 2283 7330 | N 2283 7430 | N 2283 7515 |
| N 2283/7 | Each € | | | |
| Depth x height | mm | 280x120 | 380x154 | 415x200 |
| Internal dim. LxWxh | mm | 300x220x90 | 395x320x115 | 485x355x185 |
| Weight app. | kg | 1,6 | 3 | 4,2 |

Trolley type

With built-in telescoping frame and 2 wheels

| Width | mm | 530 |
|---------------------|--------|-------------|
| Code | | N 2283 9530 |
| N 2283/9 | Each € | |
| Depth x height | mm | 355x225 |
| Dim. Internal LxDxh | mm | 510x292x175 |
| Weight approx. | kg | 5,5 |

