

ABC STORAGE Complete cabinets - Series AS 75 (54x36 units)

Width 1023 mm - Depth 725 mm

In rugged, high strength cold rolled steel sheet metal, painted
 With safety device that allows only one drawer to open at a time
 Central locking with cylinder lock
 Complete with 2 keys

As a precaution, the cabinets must be fastened to the floor or wall, especially when stacked (in this case only half capacity is allowed)

Max. load per drawer	
mm 75 P	80 kg
mm 100 P	100 kg
mm 125 P	100 kg
mm 150 T	150 kg
mm 200 T	150 kg
mm 300 T	150 kg



Height	mm	850	1000	1000	1000
Code		N 8611 6700	N 8611 7000	N 8611 8000	N 8611 9000
N 8611 - RAL 5012	Each €				
Code		N 8611 1007	N 8611 1071	N 8611 1008	N 8611 1009
N 8611/1 - RAL 9010	Each €				
With drawers	n°	7	7	8	9
Drawer composition		mm 75 P 75 P 100 P 100 P 150 T 200 T 200 T	mm 75 P 75 P 100 P 100 P 150 T 200 T 200 T	mm 75 P 75 P 100 P 100 P 100 P 100 P 100 P 100 P 150 T 200 T	mm 100 P 100 P 100 P 100 P 100 P 100 P 100 P 100 P 100 P 100 P

Height 1325 mm

With drawers	n°	9	11
Code		N 8612 9000	N 8612 1100
N 8612 - RAL 5012	Each €		
Code		N 8612 1009	N 8612 1011
N 8612/1 - RAL 9010	Each €		
Drawer composition		mm 100 P 100 P 100 P 100 P 100 P 125 P 150 T 150 T 200 T 200 T	mm 75 P 75 P 75 P 75 P 75 P 75 P 100 P 100 P 100 P 150 T 150 T 150 T 200 T

ABC STORAGE Cabinets with wheels - Series AS 75 (54x36 units)

Width 1023 mm (1198 mm with handles) - Depth 725 mm

Height 1120 mm

Cabinet capacity 600 kg

With 4 wheels in elastic rubber Ø 160 mm, including 2 swivel wheels with brake, fitted on ball bearings

Drawers as per height shown below, with single lock system

Top in sheet metal, with 4 edges with ribbed rubber mat

Steel handles coated with impact resistant rubber

Cylinder lock with 2 keys

Anti-tilt safety system



With drawers	n°	4	5	6
Code		N 8613 4000	N 8613 5000	N 8613 6000
N 8613 - RAL 5012	Each €			
Code		N 8613 1004	N 8613 1005	N 8613 1006
N 8613/1 - RAL 9010	Each €			
Drawer composition		mm 150 T 150 T 150 T 300 T	mm 100 P 150 T 150 T 150 T 200 T	mm 75 P 75 P 100 P 150 T 150 T 200 T

P = partial extraction (85%) T = total extraction (100%)