

UPRIGHTS - Slots every 25 mm - Width 53 mm

Made of two **painted steel profiles** connected together by a cross-bar for higher stability
Supplied with screws

N 8932 - For **Series AS 251 (36x36), AS 252 (54x36), AS 253 (64x36)** - Depth 705 mm

N 8945 - For **Series AS 250 (36x27), AS 255 (54x27)** - Depth 555 mm

Height	mm	1000	1500	2000	2200	2500	3000
Code	N 8932	1000	1500	2000	—	2500	3000
N 8932	Each €						
Code	N 8945	1000	1500	2000	2200	2500	3000
N 8945	Each €						

SIDE WALLS - In painted steel sheet metal

They are mounted to the uprights to close the shelf - Thickness 23 mm

N 8933 - For **Series AS 251 (36x36), AS 252 (54x36), AS 253 (64x36)** - Depth 705 mm

N 8946 - For **Series AS 250 (36x27), AS 255 (54x27)** - Depth 555 mm

Height	mm	1000	1100	1250	1500
Code	N 8933 1000	—	—	N 8933 1250	N 8933 1500
N 8933	Each €				
Code	N 8946 1000	N 8946 1100	N 8946 1250	N 8946 1500	
N 8946	Each €				

REAR WALLS - In painted steel sheet metal - Gray RAL 7000

They prevent pieces from falling down and provide higher longitudinal strength - They are fixed to the uprights with the screws supplied

Supplied in plates, about 500 mm high, to have several overall heights

N 8934 - For **Series AS 250 (36x27), AS 251 (36x36)** - Width 714 mm

N 8947 - For **Series AS 252 (54x36), AS 255 (54x27)** - Width 1020 mm

N 8962 - For **Series AS 253 (64x36)** - Width 1190 mm

Height	mm	1000	1500	2000	2200	2500	3000
Code	N 8934	1000	1500	2000	—	2500	3000
N 8934	Each €						
Code	N 8947	1000	1500	2000	2200	2500	3000
N 8947	Each €						
Code	N 8962	1000	1500	2000	—	2500	3000
N 8962	Each €						

SUPPORT SHELVES - Height 46 mm - Load capacity 250 kg

In painted steel sheet metal

They are mounted to the top, bottom and at half height of the uprights with the bolts supplied

N 8936/1 - For **Series AS 250 (36x27)** - Dimensions LxD 661x555 mm

N 8937/1 - For **Series AS 251 (36x36)** - Dimensions LxD 661x705 mm

N 8948/1 - For **Series AS 255 (54x27)** - Dimensions LxD 967x555 mm

N 8957/1 - For **Series AS 252 (54x36)** - Dimensions LxD 967x705 mm

N 8964/1 - For **Series AS 253 (64x36)** - Dimensions LxD 1137x705 mm

Code	N 8936 1000	N 8936/1	Each €
Code	N 8937 1000	N 8937/1	Each €
Code	N 8948 1000	N 8948/1	Each €
Code	N 8957 1000	N 8957/1	Each €
Code	N 8964 1000	N 8964/1	Each €

INTERMEDIATE SLOTTED SHELVES - Height 35 mm - Load capacity 300 kg

In painted steel sheet metal

They are fixed on the uprights through the supplied hooks and they can be moved to any position, by changing the shelf position

The slots are designed for inserting the dividers N 8980

They make the shelf stronger and more solid

N 8936/2 - For **Series AS 250 (36x27)** - Dimensions LxD 661x555 mm

N 8937/2 - For **Series AS 251 (36x36)** - Dimensions LxD 661x705 mm

N 8948/2 - For **Series AS 255 (54x27)** - Dimensions LxD 967x555 mm

N 8957/2 - For **Series AS 252 (54x36)** - Dimensions LxD 967x705 mm

N 8964/2 - For **Series AS 253 (64x36)** - Dimensions LxD 1137x705 mm

Code	N 8936 2000	N 8936/2	Each €
Code	N 8937 2000	N 8937/2	Each €
Code	N 8948 2000	N 8948/2	Each €
Code	N 8957 2000	N 8957/2	Each €
Code	N 8964 2000	N 8964/2	Each €

Assembly excluded

