

ABC STORAGE Computer cabinets

Width 717 mm - Depth 635 mm

In high strength cold rolled steel sheet metal, painted

Suitable for protecting monitors, keyboards, printers, etc. from dust and other pollutants

With 4-rail cable ducts

Consisting of:

- **upper compartment** internal dimensions 690 x 600 x 580h mm
 - monitor housing up to 21", with door in non-reflective polycarbonate glass and cylinder lock with 2 keys
 - 1 pull-out keyboard shelf with cover and 2-position lock, usable dimensions 620 x 510 mm
 - 1 height adjustable internal shelf, load capacity 100 kg
- **lower compartment** internal dimensions 690 x 600 x 720h mm
 - housing for printers and peripherals, with hinged doors and cylinder lock with 2 keys, closing and opening the lower door and the keyboard compartment
 - 1 pull-out shelf, load capacity 50 kg
 - 1 adjustable shelf, load capacity 100 kg

Complete with **electrical system with 5 Schuko sockets with circuit breaker and cooler fan with dust filter**

Operating temperature: -5÷+40°C with 50% humidity
-5÷+20°C with 90% humidity

Height 1560 mm

Without wheels

Code N 9025 1000	N 9025/1	Each €		1
------------------	----------	--------	-----------------------------------------------------------------------------------	---

Height 1690 mm

4 nylon wheels Ø 100 mm, including 2 swivel wheels, brake device and push handle

Code N 9025 2000	N 9025/2	Each €		1
------------------	----------	--------	-----------------------------------------------------------------------------------	---

Shelves for computer cabinets - Color gray RAL 7000

N 9026/1 - Height adjustable - Capacity 100 kg


Working space 685x510 mm - Supplied with hooks

N 9026/2 - Extendable - Capacity 50 kg

Working space 620x510 mm - Supplied with telescopic guides

Code N 9026 1000	N 9026/1	Each €		1
------------------	----------	--------	-------------------------------------------------------------------------------------	---

Code N 9026 2000	N 9026/2	Each €		1
------------------	----------	--------	-------------------------------------------------------------------------------------	---



The lock closes and opens at the same time the lower door

The electrical system (protection level Ip 30) is equipped with a 230 V AC 10A circuit breaker.

Each system is tested using a special instrument, according to IEC 60204-1 with the following tests:

- continuity of the protection circuit equipotential
- applied voltage
- insulation resistance



ABC TOOLS Extension sockets

With **6 10/16A Schuko sockets, transversal (45°)** to facilitate plug insertion, **ON/OFF safety switch** with light and 16A bipolar plug

E 1067/8 - Standard type, in plastic

With cable length 1,4 m - Overall length 340 mm

E 1067/9 - Professional type with anodized aluminium body

Suitable for EDP, PC, peripherals, video systems, etc.

Cable length 3 m, section 3x1,5 mm²

With holes to hang on wall - Overall length 430 mm

Code E 1067 8000	E 1067/8	Each €		1
------------------	----------	--------	-------------------------------------------------------------------------------------	---

Code E 1067 9000	E 1067/9	Each €		1
------------------	----------	--------	-------------------------------------------------------------------------------------	---

E 1 → pag. 445



E 1067/8



E 1067/9

ABC STORAGE Work chairs

Padded and upholstered with fire-resistant fabric

Certified according to Legislative Decree no. 81/08

Anthracite (other colours available on request)

Adjustable height range 420÷550 mm

Code N 9084 1200	N 9084/12	Each €		1
------------------	-----------	--------	-------------------------------------------------------------------------------------	---

STOOL

With feet and footrest

Gas lift bar

With seat in composite beech panels Ø 350x18 mm

Stable footrest in non-slip plastic with height adjustment, fall prevention

Adjustable height range 550÷800 mm

Code N 9085 0000	N 9085	Each €		1
------------------	--------	--------	-------------------------------------------------------------------------------------	---

N 8 → pag. 981

