

**SCANGRIP**  
INNOVATION FROM DENMARK **Inspection hand lamps**

Suitable for providing a bright and powerful light beam to a specific area or in a specific angle  
For universal use on workstations, workshops, laboratories, etc.  
Power supply 220-230 V

**STARLINE model**

**9 LED SMD LG**

300 lumen - 400 lux at 0,5 m

Protection level IP 40

Ergonomic handle with non-slip rubber

Swivel hook for hanging

Power supply 220-230 V with **5 m cable** and Schuko plug

Dimensions 26x40x340 mm - Weight 600 g

Code N 9097 3500	<b>N 9097/35</b>	Each €	 1
------------------	------------------	--------	---



IP 40

**SUPERFORM model**

Slim and handy, suitable for multiple purposes

**With 6 W high-luminosity COB LED**

700 lumen - 700 lux at 0.5 m

Protection level IP 54 (against dust and water spray)

With 2 swivelling hooks and 2 magnets

Power supply 110-240 V with **5 m cable** and Schuko plug

Dimensions 31x49x290 mm - Weight 680 g

Code N 9097 3700	<b>N 9097/37</b>	Each €	 1
------------------	------------------	--------	---



IK 08

IP 54



**Tubular profile Ø 25 mm** with shockproof acrylic profile

End-covers in shockproof hard rubber

Ergonomic and comfortable design

**Light is concentrated in a 75° beam angle:** it provides almost double illumination compared to traditional 36W fluorescent tubes

**With SPOT light** for direct illumination of small parts

The technical lifetime of LEDs is approx. 100000 hours

**LINE LIGHT C model**

**Main light: 36 PLCC SMD LEDs/ 180 lumen**


SPOT light: 1 x 1 W LED / 120 lumen

Power supply 220-230V - 50 Hz

Protection level IP 54 (against dust penetration and water splashes)

Supplied with turnable hook and flexible arm with suction cup N 9097/67

Code N 9097 4000	<b>N 9097/4</b>	Each €	 1
------------------	-----------------	--------	---



IP 54

**LINE LIGHT R model**

**Main light: 16 SMD LEDs**

400 lumen - 900 lux at 0,5 m - Operating time approx. 1,5h

**SPOT light: 1 CREE XP-G2**

150 lumen - 1500 lux at 0.5 m - Operating time approx. 4 h

With magnetic switch to turn the light on or off

Rechargeable Li-ion battery, 3.7 V (2600 mAh)

Charging time about 6 h

IP 65 protection level (protected against dust and water spray)

With swivelling hook and built-in magnet

Provided with charger with USB port N 9097/85 and USB cable

Dimensions Ø 25x357 mm - Weight 220 g

Code N 9097 4500	<b>N 9097/45</b>	Each €	 1
------------------	------------------	--------	---



Magnetic switch



IP 65

Rechargeable battery

**LINE LIGHT C + R**

**Lamp with power cable connection and rechargeable battery**

**Main light: 36 SMD LEDs**

220 lumen - 600 lux at 0,5 m - Approx. operating time 4h

**SPOT light: 1 CREE XP-G2**

80 lumen - 800 lux at 0,5 m - Approx. operating time 6h

7,4 V (1400 mAh) rechargeable Lithium-ion (Li-ion) battery

Approx. charging time 4h

Protection level IP 54 (against dust penetration and water splashes)

Supplied with charger and turnable hook

Dimensions Ø 25x488 mm

Code N 9097 5500	<b>N 9097/55</b>	Each €	 1
------------------	------------------	--------	---



IP 65

Rechargeable battery