

Professional models, explosion-proof and ATEX certified

Particularly suitable for inspection and maintenance work

With body in synthetic resin, shockproof and waterproof
UK 2AAA eLED MPL-SY

 Compact size, with **super bright and long lasting LED beam**
Can be immersed in water up to 1 m

Switch on/off through rotating ring

Luminous flux 7 lm - Luminous flux max length 14 m

With 2 alkaline batteries type AAA LR 3 (approx. operation time 14h)

Clip and metal ring - Overall length 74 mm - Weight 37 g

| | | | |
|------------------|----------|--------|---|
| Code N 9098 0000 | N 9098/0 | Each € | 1 |
|------------------|----------|--------|---|



LED lamp

 IP
67

Inspection flashlights → A 3 pag. 31

Mod. UK 2 AAA ELED Pen I
Waterproof to a depth of 3 m

Switch on/off through rotating ring

Luminous flux 35 lm - Luminous flux max length 64 m

With 2 alkaline batteries AAA type LR 3 (approx. operation time 3h)

Pocket clip - Overall length 135 mm - Weight 102 g

| | | | |
|------------------|-----------|--------|---|
| Code N 9098 1100 | N 9098/11 | Each € | 1 |
|------------------|-----------|--------|---|



LED lamp

 IP
67

 Zone 1 ATEX 0174X
II 2G Ex ib IIB T4
II 2D Ex ib IIIC T60°C

UK 4AA ES Xenon - With Xenon light
Can be immersed in water up to 3 m

On/off button

Luminous flux 38 lm - Luminous flux max length 95 m

With 2 alkaline batteries type AAA LR6 (approx. operation time 4-5h)

Eyelet for attaching to the helmet with elastic band - Overall length 155 mm - Weight 156 g

| | | | |
|------------------|----------|--------|---|
| Code N 9098 2000 | N 9098/2 | Each € | 1 |
|------------------|----------|--------|---|



XENON lamp

 IP
67

 Zone 1 SEV 08 ATEX 0164
II 2G Ex e ib IIC T4
II 2D Ex ibD 21 T98°C

Mod. UK 2AA ELED Z2
With high luminosity and long life LED
LED with 2 levels of intensity: 1) 10 Lumen (operation time approx. 40h)

2) 100 Lumen (operation time approx. 10 h)

Waterproof to a depth of 3 m

ON/OFF button

 Equipped with **safety valve to release hydrogen vapour** that can be developed by the batteries in extreme conditions of prolonged use

With loops for elastics for fastening to helmet

Complete with 2 Alkaline batteries AA LR03 (included)

Overall length 108 mm - Weight 96 g

| | | | |
|------------------|-----------|--------|---|
| Code N 9098 3300 | N 9098/33 | Each € | 1 |
|------------------|-----------|--------|---|



LED lamp

 IP
67

 Zone 2
II 3G ec ic IIB T5
II 3D ic IIB T99°C

UK 4AA eLED ZOOM
Very bright and long lasting LED, with double-element projection system

Zoom function for broaden or shrink the light beam

Can be immersed in water up to 3 m

On/off button

 Supplied with **safety valve for releasing hydrogen vapours** which may develop in batteries in extreme conditions when used for long periods

Luminous flux 77 lm + Luminous flux max length 100 m

With 2 alkaline batteries type AAA LR6 (approx. operation time 4 h)

Eyelet for attaching to the helmet with elastic band - Overall length 170 mm - Weight 176 g

| | | | |
|------------------|----------|--------|---|
| Code N 9098 4000 | N 9098/4 | Each € | 1 |
|------------------|----------|--------|---|



LED lamp

 IP
67

 Zone 1
II 2G Ex e ib IIC T4
II 2D Ex ibD 21 T98°C

Mod. UK SUREFOOT
Very high luminosity and long life LED
Waterproof to a depth of 3 m

ON/OFF button

With 1 front and 1 side LEDs to illuminate the walking zone

Luminous flux 200 lumen (170 lm + 30 lm) (operation about 6,5 h)

Max length of light beam 192 m

 Equipped with **safety valve to release hydrogen** that may develop from the batteries in extreme conditions of prolonged use

Works with 4 Alkaline batteries AA LR6 (included)

With loop for helmet elastic

Overall length 152 mm - Weight 154 g

| | | | |
|------------------|-----------|--------|---|
| Code N 9098 7200 | N 9098/72 | Each € | 1 |
|------------------|-----------|--------|---|


 2nd LED lamp
to illuminate the walking zone

 IP
67

 CL I, DIV 1, GP A, B, C, D T4
CL II, DIV 1 GP E, F, G
CL III, DIV 1 1 Ex ia
-20<Ta<+40°C